



INTERNATIONAL STONEWORKS, INC.

2523 FAIRWAY PARK, SUITE 510 * HOUSTON, TEXAS 77092
TEL: (713) 956-8291 * 1-800-775-TILE * FAX: (713) 956-8293
www.intlstoneworks.com * email: sales@intlstoneworks.com

S.A.C STAIN ABSORBING COMPOUND

A Stoneworks™ Product

This product is designed to eliminate stains, such as coffee, tea, oil, grease, butter and other non-acid stains from most **marble, granite, limestone, travertine and other porous natural stones.**

Some stains may be too old or too deep to be eliminated. Should these stains not come out, INTERNATIONAL STONEWORKS might be able to remove them with our professional grinding and polishing system.

Method of Application:

- Clean the stone surface with LAVENET or LAVENET GREEN and a damp sponge
- Rinse with a damp sponge and water

White and light colored natural stones:

- Mix the STAIN ABSORBING COMPOUND (S.A.C) with undiluted bleach (or Hydrogen Peroxide 35%) to a soft paste form.
- Place the mixture on the stain and cover it with a clear plastic sheet.
- Tape the edges of the plastic wrap with masking tape to keep the moisture damp as long as possible.
- 6 to 8 hours later, remove the plastic and tape and clean the residue with a sponge with LAVENET or LAVENET GREEN stone cleaner. Rinse with clear water.
- Let area dry for 2 to 3 hours. If the stain has diminished, but is not completely gone, repeat the procedure as often as needed.

Non-white stones:

Replace the undiluted bleach with Hydrogen Peroxide 35% and follow above directions.

Caution:

- Ventilate area well, especially when using bleach and hydrogen peroxide
- Wear protective gloves
- Keep products away from children and pets
- Refer to Material Safety Data Sheet for more information

International Stoneworks will not be liable for the damage ensuing to property injury to user or any person due to the misuse or misapplication of these products.