



INTERNATIONAL STONEWORKS, INC.

2523 FAIRWAY PARK, SUITE 510 * HOUSTON, TEXAS 77092
TEL: (713) 956-8291 * 1-800-775-TILE * FAX: (713) 956-8293
www.intlstoneworks.com * email: sales@intlstoneworks.com

TILE GLOW ® #1

TILE GLOW ® #1 is a natural, non-wax compound for the honing and deep cleaning of most unglazed **Ceramic, Porcelain and Quarry Tiles**.

Tile Glow ® #1 does not contain any hazardous acids or solvents. It contains citric acid, a “natural” acid used in food preparation and cosmetics, which gives it an excellent cleaning power.

To apply **Tile Glow ® #1**, you need:

1. **Tile Glow ® #1**
2. Floor buffer (175 to 350 RPM). Water tank and splash guard optional.
Note: A heavier buffer will give you a quicker and better honing
Optimum weight of 140 lbs.
3. Wet vacuum, clean mop, bucket, wringer, floor squeegee
4. Natural hair pad

Directions

Note: The tile and baseboards should be stripped of all waxes or sealers and neutralized.

1. Cover baseboard, carpet, etc., with protective plastic and/or tape.
2. If the grout is very dirty, scrub the grout and tile with our MDR (Mineral Deposit Remover) or TGR (Tile & Grout Restorer) and a scrubbing brush. Wet vacuum and rinse.
3. Wet a 25 Sq. Ft. area of the tile. Place a handful of **Tile Glow ® #1** on the wet area (5 oz./25 Sq. Ft.)
4. Buff the **Tile Glow ® #1** slurry with a natural hair pad for 10 to 15 minutes per 25 Sq. Ft.
5. Squeegee the **Tile Glow ® #1** slurry to the adjacent area and repeat process. Add **Tile Glow ® #1** and water as needed.
6. Vacuum-dry the **Tile Glow ® #1** mixture. Wet again honed area and buff again with the same pad without adding more **Tile Glow ® #1** to remove residue. Adding some MDR or TGR (1 pint per 5 gallons of water) will speed up the rinsing process and further clean the grout.
7. Vacuum-dry thoroughly, damp mop and let dry.

Following the honing with **Tile Glow ® #1**, polish the tiles with **Tile Glow ® #2**.

Note: Tile Glow ® #1 is available in white, gray or black to suit grout colors.

Technical Specifications: see Material Safety Data Sheet. Store in a dry place.

Precaution: The use of gloves and protective goggles is recommended when using Tile Glow® #1.

Warning: Avoid contact with skin, eyes and clothes. In case of contact, flush thoroughly with water and call Physician. Do not swallow. Keep out of children's reach.

International Stoneworks, Inc., will not be liable for any damage ensuing to property or injury to operator or any other person due to the misuse or misapplication of Tile Glow® #1 or any other chemical sold by them.