



INTERNATIONAL STONEWORKS, INC.

8650 FAIRBANKS NORTH HOUSTON HOUSTON, TEXAS 77064

TEL: (713) 956-8291 1-800-775-TILE FAX: (713) 956-8293

www.intlstoneworks.com email: sales@intlstoneworks.com

Fivextra® Plus

Fivextra® Plus Instructions

Fivextra® Plus is a no-wax UNIVERSAL medium acid compound for the polishing, hardening and protection of marble, travertine, polished limestone, and terrazzo.

Fivextra® Plus:

Eliminates grout haze on newly installed marble surfaces.

Polishes, hardens, and enhances the color of surfaces.

Does not reduce the gloss of new highly polished marble surfaces.

To apply Fivextra® Plus you will need: Fivextra® Plus compound and

1. IS-17, 200 RPM weighted floor buffer equipped with a water tank
2. Natural hair and white buffing pad
3. Wet vacuum cleaner, mop, bucket, wringer, floor squeegee

Note: Strip off all wax and sealers from the stone with Zoom or Strip & Go® and neutralize.

DIRECTIONS: Option I: WET POLISHING

1. Cover baseboard, carpet, etc., with protective plastic and/or tape
2. Wet marble surface. Sprinkle FIVEXTRA® PLUS powder on the floor (2oz./10 sq. ft.) over an area of about 25 Sq. Ft. at a time.
3. The FIVEXTRA® PLUS / water mixture should make a wet slurry. Buff the FIVEXTRA® PLUS mixture with a natural hair pad for 10-15 minutes.
4. Check the level of gloss with a squeegee. When the desired level of gloss is achieved, squeegee the FIVEXTRA® PLUS mixture to the adjacent area and repeat process. Add FIVEXTRA® PLUS and water as needed
5. Vacuum dry the FIVEXTRA® PLUS mixture. Flood rinse the polished area and buff again with the same pad without adding more FIVEXTRA® PLUS.
6. Vacuum-dry, damp mop and let dry
7. Buff polished area with a dry white pad.

DIRECTIONS: Option II: Dry Polishing

Place two ounces of Fivextra® Plus on the floor and buff immediately with the natural hair pad until dry and polished.

To reduce pad friction, if any, spray a few drops of water during the polishing process.

To restore worn marble surfaces, grind the stone first then polish the marble with Fivextra® Plus as per instructions.

SUBSEQUENT MAINTENANCE

See Marbrosol or Buff & Go®Plus information sheets

Technical Specifications:

Active Ingredients: Aluminum Oxide, Oxalic acid

pH: 3

Productivity: About 150 Sq. Ft. / hr.

For further specifications see Material Safety Data Sheet

STORE IN A DRY SPACE

PRECAUTIONS: THE USE OF GLOVES AND PROTECTIVE GOGGLES & CLOTHING IS RECOMMENDED WHEN USING FIVEXTRA® PLUS

THE USE OF RESPIRATORS, SUCH AS SELF CONTAINED BREATHING APPARATUS, IS RECOMMENDED.

WARNING: AVOID CONTACT WITH SKIN, EYES, CLOTHES. IN CASE OF CONTACT FLUSH THOROUGHLY WITH WATER AND CALL PHYSICIAN. DO NOT SWALLOW. KEEP IT OUT OF REACH OF CHILDREN AND PETS.

INTERNATIONAL STONWORKS, INC., WILL NOT BE LIABLE FOR ANY DAMAGE ENSUING TO PROPERTY OR INJURY TO OPERATOR DUE TO THE MISUSE OR MISAPPLICATION OF THE FIVEXTRA® PLUS OR OTHER CHEMICALS SOLD BY INTERNATIONAL STONWORKS, INC.

All contents of this Website © copyright 2022 by International Stoneworks, Inc. and WebShark®, and may not be used or reproduced without written permission.