



International Stoneworks

2523 Fairway Park Dr # 510

Houston, TX 77092 USA

1-(713) 956-8291

PRODUCT DATA SHEET

SEAL & GO® W

Seal & Go® W

WATER-BASED PREMIUM IMPREGNATOR

DESCRIPTION Seal & Go® W is a water-based VOC compliant impregnator that provides maximum protection for all interior/exterior natural stone, marble, granite, limestone, brick, slate, saltillo, unglazed tile, grout and masonry surfaces while preserving its natural appearance. Seal & Go® W is not a surface coating but forms a vapor permeable barrier that resists stains and makes cleaning easier.

ADVANTAGES

- حـ Apply and saturate all surfaces with Seal & Go® W allowing it to puddle and completely saturate the entire surface. Seal & Go® W can be applied with a paint brush, paint roller, paint pad/applicator, clean towel or low pressure sprayer with no more than 25 psi. **Note: Do NOT Aerosolize.**
- ضـ Allow Seal & Go® W to absorb and penetrate the entire surface 15-30 minutes. Wipe up any excess by wiping the surface with a clean towel.
- طـ Allow a minimum of 30-40 minutes drying time.

TYPICAL APPLICATIONS

- طـ Apply a second coat of Seal & Go® W to the entire surface allowing it to penetrate and absorb. Make sure all surfaces are evenly coated. Some areas may absorb more quickly than others. Let sit 15 minutes and wipe up excess with a clean dry towel.
- طـ Allow 24 hours for Seal & Go® W to completely dry and cure for best results.

COVERAGE

Application rates for natural stone, tile, grout and masonry will vary depending on the porosity of the substrate to be treated. Some stone and grout areas will absorb more quickly than other areas.

Approximate Coverage Per Coat

Low Porosity	800-1000	sq. ft./gallon
Medium Porosity	400-800	sq. ft./gallon
High Porosity	100-400	sq. ft./gallon

Note: Less impregnator will be needed when applying a second coat.

Re-apply Seal & Go® W every 2-5 years or as needed basis depending on area usage.

MAINTENANCE

Natural stone needs to be cared for properly. Seal & Go® W is not an absolute barrier to all spills, stains and soils, however natural stone, tile, grout and

masonry will repel stains and soils effectively when proper cleaning products and methods are used. This application does not eliminate the need for routine cleaning and maintenance. **International Stoneworks** makes a full range of products for stone protection and maintenance.

SAFETY

PRECAUTIONS

- ☞ KEEP OUT OF REACH OF CHILDREN.
 - ☞ Protect and cover surfaces not to be treated by this product.
 - ☞ Do not use this product with high pressure sprayers. Use low pressure sprayers with no more than 25 psi. Do not Aerosolize.
 - ☞ Do not breathe spray or mist. Use this product with adequate ventilation.
 - ☞ Use only as directed. Wear protective gloves and goggles when using. Avoid eye and skin contact. Do not breathe mists or spray. Keep container closed when not in use.
-

TECHNICAL SUPPORT

For additional technical support, contact International Stoneworks at 1-(713) 956-8291 Monday – Friday from 8:30am-5:00pm CST.

The information contained herein is based upon practical experience with Seal & Go® W. It does not constitute a guarantee. Purchasers shall determine the suitability of such products for their own purposes. User assumes all risks and liability whatsoever in connection therein. Manufacturer shall not be liable for any injury or inability to use this product.